

Stop manually restarting your router! Automated managed service re-boot device for modems, routers and switches. Automate the process to ensure highly reliable internet connection uptime.



TECHNICAL SPECIFICATIONS

Connectivity: LTE-M/NB-IoT, 700-2200MHz

Voltage: 120VAC 50/60Hz

Rated Current: up to 10 Amps

Plug Type B

Socket Type: NEMA 5-15R

Certifications: FCC part 15B, ICES-003, CE 2014/53/EU

Safety: ANSI/UL 60950, CAN/CSA-C22.2

Network: PTCRB (US), GCF (Global)

Operating Temp: 0 to 70C (32°F to 158°F)

Conforms to RoHS (2011/65/EU)

Dimensions: 5.25"(133.6mm) long, 2.44"(61.875mm) wide, 1.57"(40mm) tall

Regions: North America

Made in the USA

PRODUCT OVERVIEW

- **4G / LTE for out of band management** – No connection required to your LAN or WAN
- **Cellular network agnostic** – Dynamically chooses the best carrier per location
- **Fully managed** - Combined with Acuative managed services provides an automatic reboot when the network is down or self-operated through the Acuative customer portal
- **Hands off involvement** – Reduces the requirement to send an engineer to site or the local manager to get involved
- **Out of hours operations** - Works when the location is closed or locked – controlled remotely
- **Plug and play** - No configuration required at site
- **Cloud-based management platform** – Easy to use interface

WHY ACUATIVE?



Industry Experience

Leverage our 40 years of experience delivering transformative lifecycle network support for large, geographically dispersed networks



Global Expertise

No need to expend time and resources to tackle it alone, anywhere in the world. Acuative is your single source provider.



Technology Partners

Working closely with industry leading service providers and technology companies to deliver a seamless solution.



Tools to Manage Business Outcomes

We give you visibility to our tools and systems, with experienced project managers and our state of the art management portal.